

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	1620	(electrode) near3 (side top upper) near3 (plate).clm.	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 14:55
L2	265	1 and (force load strain stress pressure) near3 (sens\$5 detect\$5 measur\$5 transducer cell gauge)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 14:56
L3	90	1 and (force load strain stress pressure) near3 (sens\$5 detect\$5 measur\$5 transducer cell gauge). clm.	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 14:56
L4	42	3 and (base support).clm.	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 14:56

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	104382	(force load strain stress pressure) near3 (detect\$5 sens\$5 transducer cell gauge measur\$5).clm.	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:47
L2	2471	1 and ("x-axis")	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:34
L3	2025	2 and ("y-axis")	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:34
L4	811	3 and ("z-axis")	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:35
L5	572	4 and (distance)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:47
L6	464	5 and (CPU ECU processor microprocessor computer processing)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:47
L7	327	6 and (angle)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:35
L8	278	7 and (plate sheet flat)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:36
L9	240	8 and (plane)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:36
L10	67	9 and (electrode)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:36
L11	63	10 and (fixed stationary)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:36
L12	63	11 and (mov\$6 displac\$6)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:37

L13	28	12 and (capacitance capacitive)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:38
L14	16	13 and (slit slot opening)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:38
L15	15	14 and (beam bar rod)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:44
L16	245739	(fixed stationary) near3 (plate)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:45
L17	19114	16 and (fixed stationary) near3 (top upper) near3 (plate)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:45
L18	6613	17 and (mov\$6 displac\$6) near3 (plate)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:46
L19	5260	18 and (support base)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:46
L20	1543	19 and (mov\$6 displac\$6) near3 (top upper) near3 (plate)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:47
L21	59	20 and (force load strain stress pressure) near3 (detect\$5 sens\$5 transducer cell gauge measur\$5). clm.	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:47
L22	40	21 and (distance)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:47
L23	14	22 and (CPU ECU processor microprocessor computer processing)	US-PGPUB; USPAT; EPO; JPO; DERWENT	OR	ON	2005/05/04 11:47